



Individual Swivelling Mechanism for greater flexibility and customisation



Rectangle Housing

	BA | AR111 Bulb
CRI	Ra > 80 / R9 > 0
Input Power (AC)	180-265V 50/60Hz
Power Factor	> 0.9 @240VAC
Working Temp	Ambient Temperature Max 50°C
Projection Angle	38°
Remark	Ask fo TRIAC Dimming & Zigbee Wireless Dimming option

Adjustable Fitting Configuration



Single Round Fitting
Part No: BAF-R1
Size: 170mm (Ø)
Opening: 155mm (Ø)
Weight: 500g



Single Square Fitting
Part No: BAF-S1
Size: 175mm x 175mm
Opening: 155mm x 155mm
Weight: 500g



Double Fitting
Part No: BAF-S2
Size: 325mm x 175mm
Opening: 305mm x 155mm
Weight: 1000g



Triple Fitting
Part No: BAF-S3
Size: 475mm x 175mm
Opening: 455mm x 155mm
Weight: 1500g

Part No	Wattage	Colour Temp	Lumens	Lumens Per Watt	Input Power (AC)	Warranty
BA1500C	12	5700K	1500	125	240V @ 50mA	2 Years
BA1500N		4000K				
BA1500W		3000K	1350	112		
BA3000C	27	5700K	3300	125	240V @ 116mA	
BA3000N		4000K				
BA3000W		3000K	3000	112		

Note: * ± 10% Lux accuracy * Test environment @ 25°C *Specifications subject to change without prior notice.
* Product images are for illustraton purposes only.