





	DL | Downlight
CRI	Ra > 80 / R9 > 0
Input Power (AC)	180-265V 50/60Hz
Power Factor	> 0.9 @240VAC
Working Temp	Ambient Temperature Max 50°C
Projection Angle	60°
Housing Material	Die Cast Aluminium (Heatsink), Reflector & Glass
Remark	Ask for TRIAC Dimming & Zigbee Wireless Dimming option



Round Face Plate



Square Face Plate

Part No	Wattage	Colour Temp	Lumens	Lumens Per Watt	Input Power (AC)	Dimension / Size	Opening Hole	Weight	Warranty
DL1500C4	12	5700K	1500	125	240V @ 50mA	ROUND 105mm (ø) x 5.5mm (H)	95mm	300g ± 5%	2 Years
DL1500N4		4000K							
DL1500W4		3000K	1300	112					
DL1500C4S		5700K	1500	125	240V @ 50mA	SQUARE 105mm (W) x 105mm (L) x 5.5mm (H)			
DL1500N4S		4000K							
DL1500W4S		3000K	1300	112					

Note: * ± 10% Lux accuracy * Test environment @ 25°C *Specifications subject to change without prior notice.
* Product images are for illustraton purposes only.

	DL | Downlight 6' / 8"
CRI	Ra > 80 / R9 > 0
Input Power (AC)	180-265V 50/60Hz
Power Factor	> 0.9 @240VAC
Working Temp	Ambient Temperature Max 50°C
Projection Angle	120°
Housing Material	Stamped Aluminium (Heatsink) PC Diffuser, ABS Ring
Remark	Ask for TRIAC Dimming & Zigbee Wireless Dimming option



DL (6" diameter)
DL (8" diameter)



DQ Square (6")
DQ Square (8")

Part No	Wattage	Colour Temp	Lumens	Lumens Per Watt	Input Power (AC)	Dimension / Size	Opening Hole	Weight	Warranty
DL1000C6	9	6500K	1120	125	240V @ 40m	6" @ 190mm (ø) x 55mm (H)	165mm	110g	2 Years
DL1000N6		4000K	1120	125					
DL1000W6		3000K	1000	112					
DL1500C6	12	6500K	1500	125	240V @ 50mA				
DL1500N6		4000K	1500	125					
DL1500W6		3000K	1350	112					
DL2000C8	18	6500K	2250	125	240V @ 75mA	8" @ 235mm (ø) x 55mm (H)	210mm	140g	
DL2000N8		4000K	2250	125					
DL2000W8		3000K	2020	112					
DL3200C8	28	6500K	3360	120	240V @ 120mA				
DL3200N8		4000K	3360	120					
DL3200W8		3000K	3030	112					

	DN | Downlight 8" / 10"
CRI	Ra > 80 / R9 > 0
Input Power (AC)	180-265V 50/60Hz
Power Factor	> 0.9 @240VAC
Working Temp	Ambient Temperature Max 50°C
Projection Angle	60°
Housing Material	Stamped Aluminium Body, Glass
Remark	Ask for TRIAC Dimming & Zigbee Wireless Dimming option



DN (8" diameter)



DN (10" diameter)

Part No	Wattage	Colour Temp	Lumens	Lumens Per Watt	Input Power (AC)	Dimension / Size	Opening Hole	Weight	Warranty
DN3800C8	30	5700K	3800	126	240V @ 130mA	8" @ 230mm (ø) x 155mm (H)	200mm	1800g	2 Years
DN3800N8		4000K							
DN3800W8		3000K	3500	116					
DN3800C10		5700K	3800	126		10" @ 280mm (ø) x 155mm (H)	250mm	2000g	
DN3800N10		4000K							
DN3800W10		3000K	3500	116					
DN7000C8	60	5700K	7200	120	240V @ 250mA	8" @ 230mm (ø) x 155mm (H)	200mm	1800g	
DN7000N8		4000K							
DN7000W8		3000K	6720	112					
DN7000C10		5700K	7200	120		10" @ 280mm (ø) x 155mm (H)	250mm	2000g	
DN7000N10		4000K							
DN7000W10		3000K	6720	112					

Note: * ± 10% Lux accuracy * Test environment @ 25 °C *Specifications subject to change without prior notice. * Product images are for illustraton purposes only.