CooLED www.cooled.my **TL** | Track Light





	TL | Track Light
CRI	Ra > 80 / R9 > 0
Input Power (AC)	100-240V 50/60Hz
Power Factor	> 0.95 @240VAC
Working Temp	Ambient Temperature Max 50°C
Projection Angle	38°
Fitting Colour	Black or White
Housing Material	Die Cast Aluminium Base (Heatsink), Reflector & Glass



Connecters

Part No	Wattage	Colour Temp	Lumens	Lumens Per Watt	Input Power (AC)	Dimension / Size	Fitting Colour	Weight	Warranty
TL1500C	12	5700K	1500	125	240V @ 50mA	115mm (W) x 130mm (H)	White	475g ± 5%	2 Years
TL1500N		4000K							
TL1500W		3000K	1350	112					
TL1500CB		5700K	1500	125	240V @ 50mA	115mm (W) x 130mm (H)	Black	475g ± 5%	
TL1500NB		4000K							
TL1500WB		3000K	1350	112					
TL3000C	28	5700K	3080	110	240V @ 116mA	145mm (W) x 170mm (H)	White	935g ± 5%	
TL3000N		4000K							
TL3000W		3000K	2865	102					
TL3000CB		5700K	3080	110	240V @ 116mA	145mm (W) x 170mm (H)	Black	935g ± 5%	
TL3000NB		4000K							
TL3000WB		3000K	2865	102					

Note: * ± 10% Lux accuracy * Test environment @ 25 °C *Specifications subject to change without prior notice. * Product images are for illustraton purposes only.