OUTDOOR **WL | Outdoor Wall Light** SERIES · WL24-ARC

APPLICATIONS

- Residential Façades & Porches
- Walkways & Garden Walls
- Hotel & Commercial Entrances
- Perimeter & Car Park Walls

Up-Down Outdoor Wall Light

A die-cast wall luminaire with independent up and down optics for façades, corridors and entrances. Sealed IP65 body, integral surge protection and an optional dusk-to-dawn photocell.

2,640 lm
LUMINOUS FLUX (3000K)

24 W
SYSTEM POWER

110 lm/W
EFFICACY

IP65
INGRESS PROTECTION



COMMON SPECIFICATIONS

Shared across both colour temperatures

Input Voltage	220 – 240 V AC · 50/60 Hz	**Power Factor**	> 0.92
THD	< 15 %	**Optic**	Up / down asymmetric, 2 × 60°
CRI	Ra > 80	**Housing**	Die-cast aluminium, powder coated
Finish	Matt black / matt grey	**Lens**	Tempered glass, 4 mm
IP Rating	IP65	**Mounting**	Surface, 100 × 55 mm mounting base
Mounting Height	2.2 – 3.5 m	**Working Temp.**	–20 °C to +45 °C

MODELS

24 W in two colour temperatures · ± 5 % lumen tolerance

PART NO.	WATTAGE	COLOUR TEMP.	LUMENS	LM / W	SIZE (L×W×H)	WEIGHT
WL024W	24 W	**3000 K (Warm)**	2,640	110	245 × Ø95 mm	1.4 kg
WL024N	24 W	**4000 K (Neutral)**	2,760	115	245 × Ø95 mm	1.4 kg

DRAWING

Front view · Unit: mm



WALL MOUNTING

Surface mount · Unit: mm

